

## 2010 Subaru Outback

Preliminary Specification

	<b>2.5i Models</b>	<b>3.6R Models</b>
<b>Engine</b>	2.5L Single Overhead Cam (SOHC), 16-valve, horizontally-opposed, 4-cylinder SUBARU BOXER engine, Electronic Throttle Control and i-Active Valve Lift System  PZEV equipment standard on PZEV	3.6L Dual Overhead Cam (DOHC), 24-valve, horizontally-opposed, 6-cylinder SUBARU BOXER engine, Electronic Throttle Control, Dual Active Valve Control System and Active Valve Lift System
Horsepower	170 hp @ 5,600 rpm	256 hp @ 6,000 rpm
Torque	170 lb.-ft. @ 4,000 rpm	247 lb.-ft. @ 4,400 rpm
Fuel requirement	Regular grade, 87 AKI minimum	
Fuel tank	70 L	
<b>Drivetrain</b>		
Transmission	<u>Std.</u> : 6-speed manual <u>Opt.</u> : Lineartronic™ CVT (Continuously Variable Transmission) with manual mode and paddle shifters; Standard on 2.5i Limited Package	<u>Std.</u> : 5-speed electronically controlled automatic with manual mode including paddle shifters and blipping control
Symmetrical AWD	<u>With 6MT</u> : Viscous-coupling limited-slip centre differential  <u>With Lineartronic™ CVT</u> : Electronically controlled multi-plate transfer clutch	Variable Torque Distribution
Stability control	Vehicle Dynamics Control system with Traction Control System	
<b>Chassis</b>	Unitized body construction, advanced ring shaped reinforcement frame safety structure	
Suspension	<u>Front</u> : MacPherson-type struts with internal rebound springs, lower L-arms, coil springs and stabilizer bar  <u>Rear</u> : Double wishbone with stabilizer bar	
Brakes	Power-assisted 4-wheel disc with Electronic Brake-force Distribution (EBD), 4-channel / 4-sensor ABS and Brake Assist	
Steering	Engine speed sensitive, power-assisted rack and pinion	
Wheels	All: 17-in. aluminum alloy	All: 17-in. aluminum alloy
Tires	225/60R17 98T	225/60R17 98T
<b>Exterior Dimensions</b>		
Wheelbase	2740 mm	
Length	4780 mm	
Height	1670 mm (with roof rails)	
Width	1820 mm	
Min. ground clearance	220 mm	

*Specifications are preliminary and subject to change*